



5	Nut	Steel	W2/Zn Plated
4	Long Pin	Copper	Sn Plated
3	Short Pin	Copper	Sn Plated
2	Patch	LCP	UL94V-0
1	Housing	LCP	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	150/8	50/8	7
FC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)	200/9.5	250/9.5	320/9.5
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5
间距/Pitch(mm)/绝缘范围/Insulation Range	3.5/N=0~48P		
使用温度范围/Operating temperature(°C)	-40~+130		
符合RoHS环保要求/Conform to RoHS	Yes		

SURFACE:



宁波三安电子科技有限公司
Sanan Electrical Technology Co. Ltd

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRAFT:	
NAME:	15ESARHCM-THR-3.5-XXP-1Y-00A(H)
DRAWING NO.:	
TYPE:	
SIZE: A4	mm (inch)
SCALE:	
REV	1/1
SHEET	1/1

公差/General tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50
0.1/10	±Z													