



UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	300/10
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等级/ Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	320/12	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	4	4	4
额定扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.59/5.21		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	1.0~2.5/28~12		
间距/Pitch(mm)/线数范围/Poles	5.0/N=02~24P		
剥线长度/Stripping length(mm)	7		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: SURFACE:

MAT NO.:
STATUS:
APPD:
CHKD:
DRT:

NAME:  宁波三安电子科技有限公司
Sanan Electrical Technology Co. Ltd

DRAWING NO.: MCC006G-5.08
SCALE: 1/1
REV: 1/1

公差/General tolerances(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±Z	±Z

0.1/10	±Z
--------	----