



公差表/General tolerances(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±Z'	

MATERIAL:	SURFACE:	
MAT NO.:		
STATUS:		
APPD:		
CHKD:		
DRT:		
SIZE: A4	mm	inch
TYPE:	DRAWING NO.:	REV
	ZESARM-5.08-XXP-1Y-1000A&Z(H)	1/1
	SCALE: SHEET	

宁波三安电子科技有限公司
 Sanan Electrical Technology Co. Ltd

UL/CUL 技术参数		UL/CUL Technical Data			
等级	Use Group	B	C	D	
额定电压	Rated Voltage	UV	300	-	300
额定电流	Rated Current	IA	10	-	10
导线范围	Wire Range				
单/多芯线	Solid/Stranded	AWG			
耐电压	Withstanding Voltage		1800V/1min		
IEC 技术参数					
IEC Technical Data					
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	
额定电压	Rated Voltage	UV	320	630	
额定电流	Rated Current	IA	15	15	
额定冲击电压	Rated impulse withstanding voltage	[kV]	-	4.0	4.0
导线截面积	Conductor cross section				
硬质/柔性导线	Solid/flexible	[mm ²]			
材料	Material				
绝缘材料	Insulation Material	PA66			
阻燃等级	Inflammability	UL94V-0			
导体材料	Conductor Material	铜合金 Copper alloy			
导体表面镀层	Conductive Coating	镀锡 Tin Plated			
一般参数 Other Data					
间距	Pitch	[mm]	5.08		
极数	Poles	[P]	2/24		
引线长度	Shipping Length	[mm]	-		
螺丝	Screw/扭矩 Torque(Ax)	[N.m]	-		
工作温度	Operating temperature	[°C]	-40~+105		
引脚尺寸	Pin Dimensions	[mm]	4.1		
PC板孔径	PCB Hole Diameter	[mm]	1.6		